


99/06377:09/2:691

Europäisches
PatentamtEuropean
Patent OfficeOffice européen
des brevets

4



Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

99250179.1

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts:
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN
THE HAGUE,
LA HAYE, LE

11/10/99

THIS PAGE BLANK (USPTO)



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

**Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation**

Anmeldung Nr.:
Application no.:
Demande n°: 99250179.1

Anmeldetag:
Date of filing:
Date de dépôt: 08/06/99

Anmelder:
Applicant(s):
Demandeur(s):
DEUTSCHE THOMSON-BRANDT GMBH
78048 Villingen-Schwenningen
GERMANY

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
Method for addressing a bit stream recording

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat: EP Tag: 07/09/98
Date: 04/11/98
Pays: EP Date:

Aktenzeichen: EPA 98250315
File no. EPA 98250387
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:
G11B27/32, G11B20/12, G11B27/10

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

The original title of the application reads as follows:
Method for addressing a bit stream to be recorded or being recorded
on a storage medium

THIS PAGE BLANK (USPTO)

Method for addressing a bitstream to be recorded or being recorded on a storage medium

The invention relates to a method and to an apparatus for addressing a bitstream to be recorded or being recorded on a storage medium, e.g. an optical disc.

Background

In bitstream recording one is free to subdivide the bitstream into sub-units of more regular structure. Presentation data in DVDs (digital video or versatile disc) is organised into units called Video Object Unit, denoted VOBU, or Stream Object Unit, denoted SOBU, e.g. in the DVD VR Specification for DVD Video Recording in which the units are called VOBUs. VOBUs have a variable size (data amount measured in number of sectors), but have also a variable duration (measured in number of video fields). SOBUs have a constant size, but have also a variable duration.

For data retrieval from the disc the DVD VR specification foresees a 'VOBU map' which is a table where for every VOBU in a recording the length in sectors and the duration in fields is entered.

Invention

A table for data retrieval from a storage medium can be based on bitstream data being subdivided into pieces of constant duration. 'Duration' means the difference between the arrival time of the first packet of a piece and the arrival time of the packet following immediately the last packet of that piece.

'Housekeeping' in the general context of either DVD VR recording or Stream recording is the task to translate a given

time value (presentation time in case of DVD VR recording or packet arrival time in case of Stream recording) into a disc address value where the desired data can be found.

In such systems the VOB or SOBU map or 'mapping list', denoted MAPL, can contain a specific size or a specific offset or a specific delta size or, in general, a specific address-like quantity for each of these constant-duration pieces. By storing delta values instead of the total duration at a current VOB or SOBU these entries can be described with shorter word length which helps to keep the total MAPL in a reasonable size.

A possible type of housekeeping process for these systems could include the following steps:

- By division and truncation, calculate from the given time value the index of the mapping list entry to be looked up.
- The content of the mapping list entry either directly specifies the address value to access, or all mapping list entries up to that index have to be accumulated to get the address value to be accessed.

The big disadvantage of such type of MAPL which is based on constant-duration pieces lies in the following:

- In case of a low bitrate recording the pieces of constant duration will be small in size, i.e. every piece will comprise a few data sectors only or, in the extreme, a fraction of a data sector only. The disc can contain enormous numbers of those pieces, so that the MAPL may become too big to be kept in the memory.
- In case of high bitrate recording, the pieces of constant duration are big in size, i.e. each piece will comprise many data sectors. Then, addressing one piece or another corresponds to a very coarse addressing on the (sector) scale, i.e. a piece address derived from the MAPL can be located many sectors away from the currently desired location.

-Therefore housekeeping based on constant-duration pieces can result in a too big MAPL in some cases (up to one half of the disc capacity), and can result in too coarse addressing in other cases.

- 5 It is one object of the invention to disclose a method for assigning to a given time value a storage medium address value which method avoids such disadvantages. This object is achieved by the method disclosed in claim 1.

- 10 According to the invention the mapping list MAPL is based on pieces of constant length or size, i.e. a constant number of bits per piece.

- In a medium like DVD-RAM where data are physically organised into 'ECC blocks' (ECC: error correction code) of 32kByte
15 length each, particular advantages result if the above constant size or a multiple of it is used as the constant size of a piece. However, any other constant size can be used. In this case of pieces of constant size the MAPL contains for each of these pieces of constant size a specific absolute
20 duration or, preferably, a specific delta duration which indicates the arrival time of the first packet of a piece and the arrival time of the packet following immediately the last packet of that piece.

- The housekeeping process, i.e. the computation of the target
25 VOB or SOB address includes the following steps:

- Accumulate the delta durations contained in the MAPL until the given time value is most closely reached towards the target VOB or SOB, i.e. until the sum of delta durations is less than or equal to the given time value assuming that forward scanning of the VOB or SOB entries is performed, or until the sum of delta durations is greater than or equal to the given time value assuming that backward scanning of the VOB or SOB entries is performed.
30
- 35 - The running index of this mapping list entry multiplied by the constant piece size directly results in the ad-

dress value to be accessed.

The advantages of the inventive constant-size based MAPL are:

- 5 - the MAPL size does not depend on the bitrate of the recordings,
- the MAPL addressing accuracy is constant, the granularity basically corresponds to the 'piece size constant' which can be chosen as appropriate to be constant for all types
- 10 of discs, to be constant per disc, or to be constant per recording on a specific disc.

Advantageously, the address table contains an additional initializing value to initialize the accumulation of the delta time durations.

15

In principle, the inventive method is suited for addressing a bitstream to be recorded or being recorded on a storage medium, e.g. a DVD recorder, wherein an address table is used that is based on pieces of said bitstream, and wherein:

- 20 - said pieces each include a constant amount of bits of said bitstream;
- using a running index, to each address table entry for said pieces, in particular to each address table entry except the one having the highest index, a delta time du-
- 25 ration is assigned in said address table;
- the address table contains in addition an initialisation value which allows to have a share of equal bits between a predetermined amount of MSBs of application time stamps and the same amount of LSBs of said delta time durations;
- 30 - in order to get an address value for reaching a target address said initialisation value and all delta time durations up to the nearest time duration corresponding to said address value become accumulated and the running index corresponding to the delta time duration entry re-
- 35 lated to said nearest time duration becomes multiplied by

signed integer value, e.g. 18), PAT: Packet Arrival Time,
RBN: relative byte number, RBP: relative byte position,
RLBN: relative logical block number, SCR: system clock ref-
erence, SOB: Stream Object, SOBU: Stream Object Unit,
5 SOB_E_APAT: APAT of the last AP of the SOB, SOB_S_APAT: APAT
of the first AP of the SOB, SOBU_S_APAT: APAT of the first
AP of the SOBU, STB: set top box, SUM_IAPAT = Summation of
IAPAT values, TOC: table of content.

- 10 This system is designed to satisfy the following require-
ments:

Any packet size can be supported as long as it is less than
2kByte and of constant length within a take.

- A timing mechanism, i.e. a time stamp is added to every
15 broadcast packet to enable proper packet delivery during
playback.

To enlarge the fields of applications, non-real-time record-
ing should be possible. However, in this case the STB has to
generate the Time Stamp information.

- 20 Data allocation strategy and file support real-time stream
recording.

- Many digital services require Service Information which nor-
mally is embedded in the real-time stream. To support a STB
fed by data from a DVD player, the DVD should provide addi-
25 tional space, which can be used by the STB to duplicate part
of the service information and to add additional TOC infor-
mation.

- Copy Protection must be supported. In addition, any scram-
bling performed by the service provider or the STB must be
30 kept unchanged.

User requirements can be grouped into requirements for re-
cording, requirements for playback, and requirements for ed-
iting:

Real-time Recording

- 35 The system should be designed to enable real-time recording
of digital streams. It also should allow the user to con-

said constant amount in order to compute said address value.

Advantageous additional embodiments of the inventive method
5 are disclosed in the respective dependent claims.

Drawings

- 10 Embodiments of the invention are described with reference to the accompanying drawings, which show in:
- Fig. 1 simplified overall system for DVD Stream Recording;
 - Fig. 2 basic directory and file structure;
 - Fig. 3 navigation data structure;
 - 15 Fig. 4 a stream pack;
 - Fig. 5 inventive mapping list;
 - Fig. 6 structure of this mapping list;
 - Fig. 7 mapping list example;
 - Fig. 8 comparison of several time values;
 - 20 Fig. 9 IAPAT structure;
 - Fig. 10 APAT and PAT structure;
 - Fig. 11 ATS structure.

25 Exemplary embodiments

The DVD VR stream recording system is designed to use rewritable DVD discs for recording existing digital bitstreams, editing them and playing them back as bitstreams.

30 The following abbreviations are used:

AP: Application Packet, APAT: Application Packet Arrival Time, ATS: Application Timestamp, IAPAT: Incremental APAT (delta values with 12 bit resolution), LB: Logical Block,
35 LSBs: least significant bits, MAPL: Mapping List, MSBs: most significant bits, MTU_SHFT: Mapping Time Unit Shift (an un-

catenate recordings, even if those recordings consist of different stream formats. If recordings are concatenated, a seamless or close to seamless playback possibility would be nice but is not required.

5

Navigation Support

To support navigation two pieces of information (lists) should be generated during recording:

1) An 'original' version of a play list. This list contains quite low level information, e.g. time map or (broadcast) packet order of the recording. This list is accessible by the STB and the content is understood by the DVD streamer as well as by the STB. In its original version the playlist enables the playback of a complete recording. The playlist may be accessed and extended after recording by the STB to allow more sophisticated playback sequences.

2) The second piece of information, a mapping list, is generated to support the stream recorder to retrieve packet stream chunks (cells), that are described in terms of the application domain, e.g. 'broadcast packets' or 'time'. This list is owned and understood by the DVD streamer only.

Content Description

The system should reserve space which can be used by the STB to store high level TOC and Service Information. This information is provided for the user to navigate through the content stored on disc and may contain sophisticated GUI information. The content needs not to be understood by the stream recorder. However a common subset of the TOC information, e.g. based on a character string, may be useful to be shared between STB and DVD, in order to enable the stream recorder to provide a basic menu by itself.

Playback of individual recording and playing all recordings sequentially should be possible via play list.

8, Jun. 1999
8-06-1999

17:41
PD990039-F

DTB PATENT DEPARTMENT GERMANY
+49 511 418 EP99250179.1

8

Nr. 5054

J. 1.1.00

SPEC

Player menus for entry point selection

The STB can generate a sophisticated menu based on the TOC information stored on the disc. However, it should be possible to generate a simple menu by the streamer itself, e.g. via some 'character' information which is shared by STB and DVD.

Trick play modes

The STB should be able to steer trick play via the 'play list'. Due to the nature of the broadcast stream, the trick play features may be limited to basic ones, e.g. Time Search and Title Jump.

User defined playback sequence features like programming or parental control can be supported via the play list

The DVD streamer should create the 'original version' of the play list. It also should allow extensions and modifications of the play list by the STB for more sophisticated playback features. The DVD streamer is not responsible for the content of those sophisticated playlist(s).

The system must support the deletion of single recordings on user's request. If possible, the system should allow this feature under the control of the STB.

The system may support insert editing.

In the simplified overall system of Fig. 1 an application device AD interacts via an interface IF, e.g. an IEEE1394 interface, with a streamer device STRD, i.e. a DVD recorder.

A streamer STR within STRD sends its data via output buffering & timestamping handling means BTHO to IF and receives from IF data via input buffering & timestamping handling means BTHI. AD sends its data via output buffering & timestamping handling means BTHO to IF and receives from IF data via input buffering & timestamping handling means BTHIAD.

Concerning the directory and file structure, the organisation of Stream Data and Navigation Data of DVD Stream Recording is done in a specific way such as to take into account the following:

- 5 - Any DVD Streamer device STRD has certain requirements to store its own mapping list or Streamer-specific navigation data on the disc. These data are solely for helping the retrieval of recorded data; they need not be understood or even be visible to any outside application device AD.
- 10 - Any DVD Streamer device STRD needs to communicate with the application device AD it is connected to. This communication should be as universal as possible so that the maximum possible range of applications can be connected
- 15 to the Streamer. The Navigation Data to support such communication are called Common navigation data and must be understandable by the Streamer as well as by the application device.
- 20 - The Streamer device STRD should offer to the connected application device AD a means for storing its own private data of any desired kind. The Streamer needs not to understand any of the content, internal structure, or meaning of this Application-specific navigation data.

25 Fig. 2 illustrates a possible directory and file structure where all the data comprising the disc content are. The files storing the disc content are placed under the STRREC directory which is under the root directory. Under the STRREC directory the following files are created:

- 30 - COMMON.IFO
Basic information to describe the stream content. Needs to be understood by the Application Device as well as the Streamer.
- STREAMER.IFO
- 35 Private stream object information specific to the Streamer Device. Needs not to be understood by the Appli-

cation Device.

- APPLICAT.IFO

Application Private Data, i.e. information that is specific to the Application(s) connected to the Streamer.

5 Needs not to be understood by the Streamer.

- REALTIME.SOB

Recorded real-time stream data proper.

Note that except for the files described above, the STRREC directory shall not contain any other files or directories.

10

Concerning the navigation data structure, Navigation data is provided to control the recording, playing back, and editing of any bitstreams that are recorded. As shown in Fig. 3, Navigation Data includes Stream Management Information (SMI) as contained in the file named COMMON.IFO and Stream Object Information (SOBI) as contained in the file named STREAMER.IFO. From the point of view of the Streamer Device, these two kinds of information are sufficient to perform all necessary operations.

15

20

In addition to these, DVD Stream Recording also foresees the possibility of reserving a storage location for Application Private Data (APD), which may in general also be considered as Navigation Data.

25

SMI and SOBI are the Navigation Data which are directly relevant for the Streamer operation. SMI includes three kinds of information tables, namely Stream Manager General Information (SM_GI), Stream Title Table (STT), and Stream Playlist Table (SPLT), in this order. SOBI includes two kinds of information tables, namely Stream Object General Information (SOB_GI) and Mapping List (MAPL), in this order. There is no restriction in Stream Recording that each table within Navigation Information must be aligned with a sector boundary.

30

35

SM_GI includes information items like end address of SMI, end address of SM_GI, start address of STT and start address of SPLT.

STT includes information items like Number of Stream Titles, End Address of Stream Title Table, Application Packet Size, Service ID, Application Device ID, Stream Duration, Stream Name Search Pointer, Stream Title Names (STN).

- 5 SPLT includes information items like Number of Playlists, End address of SPLT, Start Addresses of Playlist Information, Number of Playlist Entries, Index of Stream Title, Start SCR, and End SCR.
- 10 Stream Object General Information (SOB_GI) includes information items like SOB Type (SOB_TY), SOB Recording Time (SOB_REC_TM), SOB Stream Information Number (SOB_STI_N), Access Unit Data Flags (AUD_FLAGS), SOB Start APAT (SOB_S_APAT), SOB End APAT (SOB_E_APAT), first SOBU of this
- 15 SOB (SOB_S_SOBU), number of Mapping List entries (MAPL_ENT_Ns).
- MAPL_ENT_Ns describes the number of mapping list entries to follow after SOB_GI.
- 20 The purpose of the inventive Mapping List MAPL is to provide all necessary information so that given playlist entries are efficiently translated into disc address pairs, and viceversa.
- 25 It is also possible to include Application Private Data which consist of three kinds of information, namely Application Private Data General Information, a set of one or more Application Private Data Search Pointers, and a set of one or more Application Private Data Area. If any Application
- 30 Private Data exists, these three kinds of information become recorded and stored in this order in the APPLICAT.IFO file.

Stream Data include one or more Stream Objects (SOBs) each of which can be stored as a 'Program stream' as described in

35 ISO/IEC 13818-1, Systems.

A SOB can be terminated by a program_end_code. The value of

the SCR field in the first pack of each SOB may be non-zero.
A SOB contains the Stream Data packed into a sequence of
'Stream Packs' (S_PCKs). Stream data can be organised as one
elementary stream and are carried in PES packets with a
5 stream_id.

As shown in Fig. 4 a Stream Pack includes a 14-byte pack
header and a Stream PES Packet to which a 24-byte PES packet
header and a Substream ID byte belongs.

10 A Stream Object is composed of one or more Stream Packs.

The MAPL table depicted in Fig. 5 contains n pieces or SOBUs
SOBU#1 to SOBU#n of the bitstream to be recorded or of the
recorded bitstream. To SOBU#1 to SOBU#n-1 a corresponding
15 Incremental Application Packet Arrival Time entry IAPAT#1 to
IAPAT#n-1 is assigned. DAV denotes a desired address or tar-
get address in the bitstream. SOBU#1 to SOBU#n each concern
a constant number of bits of the bitstream.

20 As shown in Fig. 6, the Mapping List includes the Initial
Time of the MAPL IAPAT#0 and zero or more instances of "In-
cremental Application Packet Arrival Time" (IAPAT).

	Contents	Number of Bytes
(1) IAPAT	Incremental APAT	2
	Total	2

The structure of the IAPAT value is depicted in Fig. 9.

25 IAPAT describes the Incremental Application Packet Arrival
Time of the corresponding Stream Object Unit in DVD Stream
Recording's Incremental PAT Describing Format defined below.

For an explanation on how to calculate IAPAT(i) during re-
30 cording, the following notations will be used:

- For abbreviation, M shall denote the number of Mapping
List entries MAPL_ENT_Ns.

- SOBU_S_APAT(*i*) ($1 \leq i \leq M$) shall denote the start Application Packet Arrival Time of the Stream Object Unit #*i* of the Stream Object, i.e. the packet arrival time of the first packet belonging to the Stream Object Unit #*i*.

5 SOBU_S_APAT(1) shall be equal to the Application Time Stamp of the first Application Packet of Stream Object Unit #1 of the Stream Object.

- IAPAT(0) shall denote the initial value for the Mapping List.

10 • IAPAT(*i*) shall denote the *i*-th entry of the Mapping List, i.e. IAPAT(0) is the first and IAPAT(*M*-1) is the last entry of the Mapping List.

- SUM_IAPAT(*i*) shall denote the summation of the IAPATs from 0 to *i* ($i < M$)

15 $SUM_IAPAT(i) = IAPAT(0) + IAPAT(1) + \dots + IAPAT(i)$ (eq 1)
with $SUM_IAPAT(-1) = 0$.

Then IAPAT(*i*) shall be chosen such that
IAPAT(*i*) =

20 $\text{floor}(SOBU_S_APAT(i+1)/2^{MTU_SHIFT}) - SUM_IAPAT(i-1)$ (eq 2)
for $i = 1, 2, \dots, M-1$.

The IAPAT value range is limited by the resolution (12 bit) of an IAPAT value and its minimum value (IAPAT(*i*) = 1 for

25 $I > 0$ and $IAPAT(0) = 0$):

$0 \leq IAPAT(0) < 2^{12}$ (eq 3)

and

$1 \leq IAPAT(i) < 2^{12}$ for $i > 1$ (eq 4)

30 The floor function floor(*x*) rounds down, e.g. floor(1.2) = floor(1.8) = 1, floor(-1.2) = floor(-1.8) = -2.

SOBU_S_APAT(*i*) is described in the DVD Stream Recording PAT Describing Format. But, in evaluating the equations above they must be treated as if they were 6 byte unsigned integer

35 values.

Fig. 7 shows, along the time axis, an example of the order of SOBU, SOBU_S_APAT and IAPAT. The left side of the time axis is divided into 'Mapping Time Units' and the right side of the time axis shows the SOBUs.

- 5 Mapping Time Unit is a duration corresponding to IAPAT = 1, and can be calculated as

$$\text{Mapping Time Unit} = (2\text{MTU_SHIFT} / 90000) \text{ seconds} \quad (\text{eq 5})$$

For MTU_SHFT = 18 it corresponds to approx. 5.69 milliseconds.

10

SOB_S_APAT describes the start Application Packet Arrival Time of a Stream Object, i.e. the packet arrival time of the first packet belonging to the SOB. SOB_S_APAT is described below in the DVD Stream Recording PAT Describing Format:

- 15 PATs consist of a base part and an extension part. The base part holds the so-called 90kHz unit value, and the extension part holds the less significant value measured in 27MHz units.

(a) Choosing SOB_S_APAT for a new recording

- 20 A newly recorded SOB will normally start with the first Application Packet of a SOBU. In this case, SOB_S_APAT and the Application Timestamp of the first Application Packet of the SOB will normally be set to 0.

(b) Calculation of SOB_S_APAT after editing

- 25 After editing, e.g. deleting the start of a SOB, SOB_S_APAT, the Application Timestamp of the first Application Packet of the first SOBU of the SOB and the Application Timestamp of the first Application Packet belonging to the SOB may differ and may be not equal to 0.

30

All possible cases are covered by the following general definition of SOB_S_APAT:

- let ats_0 be the 30-bit Application Timestamp of the first Application Packet belonging to the SOB and
- 35 • let N be the number of all Application Timestamp wrap-arounds occurring between the 30-bit Application Timestamp

of the first Application Packet starting in the first SOBU
of the SOB and ats_e , i.e. $0 \leq N \leq 1$, then
 $SOB_S_APAT[MTU_SHFT + 11...0] = ats_e[MTU_SHFT + 11...0]$
 $SOB_S_APAT[48...MTU_SHFT + 12] = N$

5

With this definition of SOB_S_APAT , the APAT of the first
Application Packet starting in the first SOBU of the SOB is
equal to or greater than 0 and less than $2 \cdot MTU_SHIFT + 12$.

10 Fig. 10 shows the DVD Stream Recording PAT Describing For-
mat. The variables in this figure are defined as follows:

PAT_base: PAT's base value measured by 90kHz unit

PAT_exten: PAT's extension value measured by 27MHz unit

$(0 \leq PAT_exten < 300)$

15 $PAT \text{ in seconds} = (PAT_base/90000Hz) + (PAT_exten/27000000Hz)$

For an unique representation of times, PAT_exten must be in
the range of $0 \leq PAT_exten < 300$. Together, PAT_base and
 PAT_exten cover a range of more than 1696 hours.

20

SOB_E_APAT describes the end Application Packet Arrival Time
of the Stream Object, i.e. the packet arrival time of the
last packet belonging to the SOB, in the DVD Stream Record-
ing PAT Describing Format. The general definition of

25 SOB_E_APAT is as follows:

- let ats_e be the 30-bit Application Timestamp of the last
Application Packet belonging to the SOB and

- let N be the number of all Application Timestamp wrap-
arounds occurring between the 30-bit Application Timestamp

30 of the first Application Packet starting in the first SOBU

of the SOB and ats_e , i.e. $N \geq 0$, then

$SOB_E_APAT[MTU_SHFT + 11...0] = ats_e[MTU_SHFT + 11...0]$

$SOB_E_APAT[48...MTU_SHFT + 12] = N$

35 The Application Time Stamp (ATS) in front of each Applica-
tion packet consists of a 30-bit value. An ATS includes a

base part and an extension part. The base part holds the so-called 90kHz unit value, and the extension part holds the less significant value measured in 27MHz units.

Fig. 11 depicts the DVD Stream Recording Application Time Stamp Describing Format. The variables in this figure are defined as follows:

AU_START when set to '1', indicates that the associated Application Packet contains a random access entry point (start of a random access unit) into the stream

AU_END when set to '1', indicates the associated Application Packet is the last packet of a random access unit

ATS_base base value of ATS measured in 90kHz units

ATS_exten extension value of ATS measured in 27MHz units

ATS in seconds = $(ATS_base/90000Hz) + (ATS_exten/27000000Hz)$

For a unique representation of times, ATS_exten must be in the range of $0 \leq ATS_exten < 300$. Together, ATS_base and ATS_exten cover a range of more than 23 seconds.

Fig. 8 depicts the value ranges of ATS, IAPAT and SUM_IAPAT with respect to the 48-bit range of APAT. ATS covers bits 0 to 29. IAPAT covers bits 18 to 29. SUM_IAPAT covers bits 18 to 47.

A significant advantage of the invention is that the mapping list generates timestamps SUM_IAPAT of which the 12 LSB bits No. 18 to 29 are identical to the 12 MSB bits No. 18 to 29 of the stream timestamps ATS. This feature allows to simplify the real-time recorder hardware.

Example function for scanning the Presentation Data until the desired Application Packet is found

The following function describes how to scan Presentation Data in order to retrieve an individual application packet associated with a Packet Arrival Time 'x'. Thereby the Map-

ping List and the access to it is described in more detail,
e.g. internal intermediate values which are required in sub-
sequent steps, see Fig. 5, 6 and 7. The main result of Map-
ping List access is the Sector offset SOFF, indicating where
5 the scanning starts. The complete scanning will be carried
out inside a given SOB.

Notes on nomenclature used:

- x48 is a 6-byte APAT value which is indicated below by
'48'.
- 10 • The value '30' attached to other variables indicates that
they consist of 30 bits, e.g. Application Time Stamp ATS.
- IAPAT(0), IAPAT(1), ... denote the entries of the Mapping
List.
- The form var[a...b] denotes the bit field between and in-
15 cluding bits a and b of the variable var.
- '[i ... k]' denotes bits i to k of a binary number, i =
MSB, k = LSB .
- '/*...*/' denotes explanatory comments.
- 20 In order to simplify the example it is assumed that each
sector contains an integer number of at least one applica-
tion packet(s).

Function get_application_packet_location(x48)

- 25 a) sum_iapat48 = IAPAT(0) * 2^{MTU_SHIFT}; k = 1
- b) ss48 = IAPAT(k) * 2^{MTU_SHIFT}
- c) if (sum_iapat48 + ss48)[47...18] ≥ x48[47...18], then
go to g)
- d) sum_iapat48 = sum_iapat48 + ss48
- 30 e) k = k + 1
- f) if k < MAPL_ENT_Ns, then go to b)
- g) soff = (k-1)*SOBU_SZ /* sector
offset of SOBU#(k) relative to the 1st SOBU of the SOB */
- h) offset48[47...30] = sum_iapat48[47...30]

18

```
i) offset48[29...0] = 0
j) current_ats30 = 0;
k) ap_no = 1
   /* Number of AP within Sector,  $1 \leq \text{ap\_no} \leq \text{AP\_Ns}$  */
5  l) previous_ats30 = current_ats30
m) current_ats30 = (ATS of the application packet #ap_no of
   sector #soff)
n) if previous_ats30 is greater than current_ats30, then
   offset48 = offset48 +  $2^{30}$  /*handle ATS wrap around */
10 o) if current_ats30 + offset48 = x48 then
   go to s) /* target found! */
p) if sector #soff contains at least one more application
   packet start, then
   ap_no = ap_no + 1
15 go to m)
q) soff = soff + 1
r) go to k)
```

The desired application packet is now retrieved as packet
20 #ap_no of sector #soff. A value of ap_no = 1 denotes the
first Application Packet starting in the Sector. A value of
soff = 0 denotes the first Sector of the first SOBU of the
SOB.

25 The above function is a more general example. It can be sim-
plified if MTU_SHFT < 19. This requirement is fulfilled be-
cause MTU_SHFT is defined as 18.

```
a) sum_iapat30 = IAPAT(0); k = 1
b) sum_iapat30 = sum_iapat30 + IAPAT(k)
30 c) if sum_iapat30  $\geq$  x48[47...18], then go to f)
d) k = k + 1
e) if k < MAPL_ENT_Ns, then go to b)
```

```
f) soff = (k-1)*SOBU_SZ /* sector off-
    set of SOBU #(k) relative to the 1st SOBU of the SOB */
g) ap_no = 1
    /* number of AP within Sector, 1 ≤ ap_no ≤ AP_PKT_Ns */
5 h) if (ATS of the application packet #ap_no of sector #soff)
    equal to x48[29...0], then
    go to l) /* target found! */
i) if sector #soff contains at least one more application
    packet start, then
10 ap_no = ap_no + 1
    go to h)
j) soff = soff + 1
k) go to g)
```

15 The desired application packet is now retrieved as packet #ap_no of sector #soff. A value of ap_no = 1 denotes the first Application Packet starting in the Sector. A value of soff = 0 denotes the first Sector of the first SOBU of the SOB.

20 The 30 bits of ATS have the same weight as the 30 LSBs of APAT.

It is not required that the first sector of the first SOBU of a SOB belongs to this SOB. If the first part of a SOB was erased, then the remaining SOB may start in the middle of a

25 SOBU, i.e. the first sector of this SOBU is not part of the SOB.

In Stream recording, the application performs its own padding, so that the pack length adjustment methods of DVD-ROM

30 Video or DVD-VR need not to be used. In Stream recording it is safe to assume, that the Stream packets will always have the necessary length.

The data stream also contains application time stamps ATS, e.g. within the data packets.

Claims

1. Method for addressing a bitstream to be recorded or being
recorded on a storage medium (STRD), wherein an address
5 table (MAPL) is used that is based on pieces (SOBU#n) of
said bitstream, characterised by:
 - said pieces (SOBU#n) each include a constant amount of
bits of said bitstream;
 - using a running index (0, 1, 2, 3, ..., n-1), to each ad-
10 dress table entry for said pieces, in particular to each
address table entry except the one having the highest in-
dex, a delta time duration (IAPAT#n) is assigned in said
address table;
 - the address table contains in addition an initialisation
15 value (IAPAT#0) which allows to have a share of equal
bits between a predetermined amount of MSBs of applica-
tion time stamps (ATS) and the same amount of LSBs of said
delta time durations (IAPAT#n);
 - in order to get an address value for reaching a target
20 address (DAV) said initialisation value (IAPAT#0) and all
delta time durations (IAPAT#1, ... IAPAT#n-1) up to the
nearest time duration value corresponding to said address
value become accumulated, and the running index (i) cor-
responding to the delta time duration entry ($\Delta DUR\#i$) re-
25 lated to said nearest time duration value becomes multi-
plied by said constant amount in order to compute said
address value.
2. Method according to claim 1, wherein said storage medium
30 (STRD) is a Streamer device or a DVD recorder.
3. Method according to claim 1 or 2, wherein said pieces
(SOBU#n) of said bitstream contain data packets and a
delta time duration value which is the difference between
35 the arrival time of the first packet of a piece and the
arrival time of the packet following immediately the last

packet of that piece.

4. Method according to any of claims 1 to 3, wherein the
size of a piece corresponds to the number of bits of an
5 ECC block or a multiple thereof.

5. Method according to any of claims 1 to 4, wherein said
initialisation value corresponds to some, in particular
12, MSBs of the application time stamp (ATS) of the first
10 application packet of the first piece (SOBU) which is de-
scribed by said address table (MAPL).

6. Method according to any of claims 1 to 5, wherein said
address table is a mapping list (MAPL).

Abstract

In bitstream recording presentation data is organised into Video Object Units. These have a variable size but have also
5 a variable duration. To allow access to any Video Object Unit in the bitstream a mapping list is used which is based on pieces (SOBU#n) of the bitstream of constant size per piece. The mapping list additionally contains for each of these pieces a specific delta duration (IAPAT#n) which indi-
10 cates the difference between the arrival time of the first packet of a piece and the arrival time of the packet following immediately the last packet of that piece, and contains an initialisation value (IAPAT#0) which allows to have a share of equal bits between a predetermined amount of MSBs
15 of application time stamps (ATS) and the same amount of LSBs of said delta time durations (IAPAT#n). The computation of the target SOBU address includes the following steps:
- accumulate the initialisation value and the delta durations until the given time value is most closely reached to-
20 wards the target SOBU;
- the running index of this table entry multiplied by the constant piece size directly results in the address value to be accessed.

25

Fig. 5

1/4



2/4




Fig.4




Fig.5




Fig.6

3/4




Fig. 8




Fig. 9




Fig. 7

4/4




Fig. 10




Fig. 11